

NASA Technical Memorandum 105140

# Qualitative Investigation of Cryogenic Injected Shock Dissipation

R.C. Hendricks  
*Lewis Research Center*  
*Cleveland, Ohio*

Prepared for the  
Cryogenic Engineering Conference  
cosponsored by the University of Alabama at Huntsville, and  
NASA Marshall Space Flight Center  
Huntsville, Alabama, June 11-14, 1991



# QUALITATIVE INVESTIGATION OF CRYOGENIC INJECTED SHOCK DISSIPATION

R.C. Hendricks  
National Aeronautics and Space Administration  
Lewis Research Center  
Cleveland, Ohio 44135

## ABSTRACT

The injection of fluid nitrogen into the flow field discharged from a two-dimensional, ambient, static-temperature and static-pressure Mach = 2.7 nitrogen flow tunnel was observed. A bow shock stands approximately one diameter off the end of the 3.2 mm o.d. x 1.6 mm i.d. injection tube placed directly into the tunnel exhaust. Cryogenic injection creates a high density region in the injected region and within the bow shock wake but the standoff distance remains unchanged. However as the temperature reaches a critical value  $T_{inj}^*$  the sharp shock interface begins to fade resembling the density gradient seen at the interface of a supercritical fluid and the shock interface begins to move into the supersonic stream. As the injection temperature decreases, the interface continues to move into the supersonic stream and becomes more diffuse; the shock interface can not be distinguished. The phenomena is completely reversible.

## INTRODUCTION

The fracturing of a supercritical-pressure water stream discharged to ambient conditions has been studied by Field and Lesser.<sup>1</sup> The shock structure is evidenced in his photographs and stream breakup is cataclysmic. Droplets are rapidly dispersed. The fracturing of sub- and supercritical-pressure, radial inward flows has been studied by Hendricks et al.<sup>2</sup> Motion pictures of the flow between parallel disks spaced 0.076 mm apart show rapid stream breakup immediately downstream of the exit plane. The flow appears finely dispersed with the potential of fluid fracture occurring within the passage. Fluid injection into high-velocity gas streams has been investigated by several authors interested in maintaining a film adjacent to the wall to provide film cooling (e.g., Papell<sup>4</sup> and Simon and Ciancone<sup>5</sup>). The injection of supercritical-pressure fluids into combustors is commonplace in rocket propulsion. In analyzing the streams, liquid is assumed to exist and to vaporize as the stream traverses the chamber.<sup>6</sup> Reichenback and Horn<sup>7</sup> related injection properties to penetrating distance for liquid injection into supersonic flow streams. Hendricks et al.<sup>8</sup> injected a M = 2.7 gaseous nitrogen flow field to determine the penetration distance with injection angles of 90 and 20 degrees to the flow. The injected fluid temperature of nitrogen was above  $T_{inj}^* = 95$  K.

From these experiments<sup>1-3,7,8</sup> it is clear that supercritical-pressure jets fracture almost immediately after discharge and that fluid streams can penetrate supersonic flow fields. It is not clear when the high-pressure stream is a cryogen and is injected directly into and opposing a supersonic gaseous flow, how the fracture will occur, or what are the effects of  $T_{inj} < T_{inj}^*$ . This paper describes a qualitative investigation into this problem.

## EXPERIMENT

The experiment is classically simple. One designs and fabricates a Mach 2.7 two-dimensional gas nitrogen tunnel and couples it with a high pressure cryogenic source. The two-dimensional tunnel,<sup>8</sup> and cryogenic source,<sup>9</sup> both using nitrogen, are illustrated schematically in Fig. 1. The tunnel operates at 2.3 to 2.4 MPa in the chamber, achieving Mach 2.7 at ambient pressure. This flow field is maintained for nearly 760 mm and discharges to ambient.




Figure 1.—Bow shock formation for gaseous nitrogen injection.

The injection tube was fabricated of 3.2 mm o.d. x 1.6 mm i.d. copper tubing. The pressure was measured prior to injection and the temperature was measured less than 1-diameter upstream from the injection plane on the outside of the copper tube. The thermocouple ball was soldered to the tube and the lead wires tightly wrapped around the tube out of the flow field.

The injection fluid was passed through a copper coiled heat exchanger in a liquid nitrogen bath open to ambient.

Calibrations indicated that the flow field Mach number was nearly 3.0 versus the 2.7 design value within the two-dimensional tunnel.

A shadowgraph scheme was devised to observe the flow field and the results were recorded on videotape. The flow field noise level was intense and strongly effected some video cameras.

## RESULTS

Figure 1 illustrates gaseous nitrogen injection into the supersonic flow field. The injection pressure is a nominal 6.9 MPa. The sharp interface of the bow shock is clear as are some aftershocks leaving the thermocouple lead wire wrapped about the injection tube.

With cryogenic injection, the injection tube is obscured and the details of the bow shock injection interface become unclear so the question of how the interface fractures can not be answered with fidelity. However the bow shock remains unchanged even though the aftershock region clearly shows a darkened region of higher density, Fig. 2. The injection temperature is above  $T_{inj}^*$ .




Figure 2.—Bow shock formation for cryogenic nitrogen injection with  $T_{inj} > T_{inj}^*$ .

As the injection temperature decreases to  $T_{inj}^*$ , the sharpness of the bow shock declines and the shock interface standoff distance increases as the shock begins to advance into the supersonic flow stream, Fig. 3.

For  $T_{inj} < T_{inj}^*$  the appearance of Mach lines and the growth of the injected region continues. The standoff distance continues to increase, Fig. 4.




Figure 3.—Incipient shock dissipation for cryogenic nitrogen injection,  $T_{inj} = T_{inj}^*$ .




Figure 4.—Shock dissipation for cryogenic nitrogen injection  $T_{inj} < T_{inj}^*$ .






Figure 5.—Dissipation to a faint interface for cryogenic nitrogen injection  $T_{inj} < T_{inj}^*$ .




Figure 6.—Dissipation of the characteristic shock front for cryogenic nitrogen injection  $T_{inj} < T_{inj}^*$ .

Decreasing  $T_{inj}$  still further, Fig. 5, only a faint resemblance of the shock region can be found.

At the lowest injection temperature provided from this system, the darkened region provides evidence of the cryogenic injection, but the shock appears dissipated, Fig. 6.

Each step of the shock dissipation can be readily retraced by increasing  $T_{inj}$  until  $T_{inj} = T_{inj}^*$  and the bow shock will reappear for all  $T_{inj} > T_{inj}^*$ . Small temperature changes about  $T_{inj}^*$  provide a shock or no shock phenomena.

## SUMMARY

The effects of injecting supercritical pressure fluid nitrogen into a supersonic flow were observed. For injection temperatures above a critical value, there was no effect on the bow shock. At the critical injection temperature the shock strength weakens significantly and at lower injection temperatures the interface is diffusive. For a fixed injection pressure, there is no change in the standoff distance until the injection temperature is less than the critical injection temperature. The observed phenomena is completely reversible. Photographic details of the interface are lacking, so how the interface fractures is not resolved.

## REFERENCES

1. J.E. Field, and M.B. Lesser, On the Mechanics of High Speed Liquid Jets. Proc. R. Soc. Lond. A. 357: 143 (1977).
2. R.C. Hendricks, R.J. Simoneau, and Y.Y. Hsu, A Visual Study of Radial Inward Choked Flow of Liquid Nitrogen, in "Advances in Cryogenic Engineering," Vol. 20, Plenum Press, New York, (1975), p. 370.
3. R.C. Hendricks, T.T. Stetz, Experiments on flow through one to four inlets of the orifice and Borda types. "Advances in Cryogenic Engineering," Vol. 27, Plenum Press (1982) p. 817.
4. S.S. Papell, "Vortex Generating Flow Passage Design for Increased Film Cooling Effectiveness," U.S. Patent 4,529,358, (1985). (See also, NASA TP-2388, 1984).
5. F.F. Simon and M.L. Ciancone, Flow Visualization Study of the Effect of Injection Hole Geometry on an Inclined Jet in Crossflow in "Heat Transfer and Fluid Flow in Rotating Machinery," Hemisphere Pub., Washington, D.C. (1987), p. 170.
6. A.J. Przekwas, S.G. Chuech, and A.K. Singhal, "Numerical Modeling for Primary Atomization of Liquid Jets," AIAA Paper 89-0163 (1989).
7. R.E. Reichenback and K.P. Horn, "Investigation of Injectant Properties on Jet Penetration in a Supersonic Stream," AIAA Journal p. 9:469 (1971).
8. R.C. Hendricks, D.R. Boldman, H.E. Neumann, and B.L. Vlcek, Qualitative Investigation of Cryogenic Fluid Injection Into a Supersonic Flow Field, in "Advances in Cryogenic Engineering," Vol. 35, part A, Plenum Press, (1988).
9. R.C. Hendricks, et al., "Experimental Heat-Transfer Results for Cryogenic Hydrogen Flowing in Tubes at Subcritical and Supercritical Pressures to 800 Pounds Per Square Inch Absolute," NASA TN D-3095 (1966).

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 1991		3. REPORT TYPE AND DATES COVERED Technical Memorandum
4. TITLE AND SUBTITLE  Qualitative Investigation of Cryogenic Injected Shock Dissipation			5. FUNDING NUMBERS  WU-505-62-52	
6. AUTHOR(S)  R.C. Hendricks				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER  E-6244	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER  NASA TM-105140	
11. SUPPLEMENTARY NOTES  Prepared for the Cryogenic Engineering Conference cosponsored by the University of Alabama at Huntsville and NASA Marshall Space Flight Center, Huntsville, Alabama, June 11-14, 1991. Responsible person, R.C. Hendricks, 216-433-5912.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Unclassified - Unlimited Subject Category: 34  Available electronically at <a href="http://gltrs.grc.nasa.gov">http://gltrs.grc.nasa.gov</a> This publication is available from the NASA Center for AeroSpace Information, 301-621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  The injection of fluid nitrogen into the flow field discharged from a two-dimensional, ambient, static-temperature and static-pressure Mach = 2.7 nitrogen flow tunnel was observed. A bow shock stands approximately one diameter off the end of the 3.2 mm o.d. x 1.6 mm i.d. injection tube placed directly into the tunnel exhaust. Cryogenic injection creates a high density region in the injected region and within the bow shock wake but the standoff distance remains unchanged. However as the temperature reaches a critical value $T_{inj}^*$ the sharp shock interface begins to fade resembling the density gradient seen at the interface of a supercritical fluid and the shock interface begins to move into the supersonic stream. As the injection temperature decreases, the interface continues to move into the supersonic stream and becomes more diffuse; the shock interface can not be distinguished. The phenomena is completely reversible.				
14. SUBJECT TERMS  Shock; Cryogenics; Injection			15. NUMBER OF PAGES 8	
			16. PRICE CODE A02	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	